



### Package Contents & Links To Instructional Videos

1. #6300, 3M 6000, 3M LOW MAINTENANCE HALF MASK RESPIRATOR, SIZE LARGE- Qty (1)



2. 3M ORGANIC VAPOR/ACID GAS CARTRIDGE/FILTER 60923, P100 RESPIRATORY PROTECTION - (Pack of 2)



You Tube videos on how to assemble, wear, and perform maintenance to the **3M Low Maintenance Half Mask Respirator** – (hold down “Ctrl” key on your keyboard while clicking on the YouTube link below)

<http://youtu.be/Ec3XilX6HM>

5. Tyvek Suit – Qty (1)



YouTube video on how to put on Tyvek protective clothing - (hold down “Ctrl” key on your keyboard while clicking on the YouTube link below)

<https://www.youtube.com/watch?v=zLbvQcpfZyQ>

# DuPont TY120S WH - 2X - Tyvek Coverall

Tychem® TK exhibits excellent chemical barrier properties and offers an extremely durable fabric that is puncture- and tear-resistant. Tychem® TK fabric shows at least 30 minutes of barrier protection to 322 challenge chemicals with no observed breakthrough. Tychem® TK is specifically developed for protection against toxic, corrosive gases, liquids and solid chemicals. This high-performance chemical barrier fabric is suited for industrial, HazMat, and domestic preparedness applications.

## Garment Features:

- Certified compliant to the 2007 edition of NFPA 1994, Class 2 Standard on Protective Ensembles for First Responders to CBRN Terrorism Incidents by an independent third party certification organization.
- Class 2 garments are designed for situations where there is an immediate danger to life and health (IDLH) and must be worn with a self-contained breathing apparatus (SCBA). This is the highest level of protection under the NFPA 1994 standard.
- Encapsulated Level A garment design is our highest level of protection from from liquid splash and vapor/gas exposures for both the wearer and respiratory equipment
- Double taped seams provide strong chemical resistance against heavy liquid splashes. A sewn seam is covered, both inside and outside of garment with compatible chemical-resistant material by heat-sealing.
- Expanded faceshield provides wide 220 degree viewing angle. EX faceshield is three-layer laminate composed of 40 mil PVC/5 mil Teflon® /20 mil PVC
- Rear entry design keeps closure away from direct contact with frontal chemical exposure and provides ability to change air bottle on SCBA without removing the entire garment
- Expanded back to accommodate self-contained air breathing apparatus (SCBA)
- Vapor tight zipper. Extra long to increase garment opening and aid donning and doffing
- Storm flap covers zipper which can be secured by the wearer with rugged hook and loop material to prevent intrusion at zipper
- Attached internal Ansell® Barrier® gloves composed of five layer laminate film for a broad range of chemical protection
- Neoprene gloves provide mechanical and physical durability to help protect inner Barrier® glove
- Integrated socks composed of garment material
- Attached flaps are designed to cover boot tops to help reduce potential for liquid intrusion
- Two exhaust valves release higher pressure inside encapsulating garments while simultaneously helping to prevent inward leakage of external vapors or particles into the garment. One-way valves are positive pressure and open on demand. Valves include splash covers made of barrier material to help prevent liquid intrusion. Valves are located on left back of head and right lower back.
- Internal adjustable waist belt system for support and improved fit
- Each suit has a unique serial number and is fully tested at time of manufacture including positive air pressure integrity testing per ASTM F1052.

6. PYRAMEX Safety Goggles – Qty (1)



GG504T

Model: Capstone

Capstone Features:

- Dual purpose goggle adjustable to many different applications.
- Removable vent caps allow the user to remove when more ventilation is required or leave in place for unsurpassed chemical resistance.
- Adjustable quick release elastic band for easy on/off
- Soft PVC body conforms to facial contour for comfort fit
- Fits over prescription eyewear.
- Exceeds the ANSI Z87.1 High Velocity Impact Standards.
- CE EN 166 Certified
- CAN/CSA Z94.3-07

Clear Lens:

- General purposes for indoor applications that require impact protection.
- Cylinder lens is coated to prevent fogging.
- Offers protection from excessive glare.
- Scratch-resistant lenses
- Provides 99% protection from harmful UV-A and UV-B rays.
- 100% polycarbonate lenses

7. 8 mil powder free nitrile gloves - Qty (3 pairs)



PosiShield High Risk powder free nitrile gloves, 8 mil, 11.5", blue, XXL.

(hold down "Ctrl" key on your keyboard while clicking on the YouTube link below)

<https://www.youtube.com/watch?v=-ELppp1QMJM>

8. Fogger – Qty(1) –



**Adjustable flow rate and fog particle size.** A precision regulating valve lets you control flow rate (0-9.5 gal/h) and particle size (5-50 micron VMD). Smaller fog particles are suited for pesticides that are effective even in low doses. Occasionally you want larger fog particles, for example an outdoor fog that is less likely to be carried away by wind.

**Comes with convenience features,** including: An 18 inch flex hose so you can spray into hard-to-reach areas like under carpets, above ceilings, and between furniture. An adjustable-length fabric strap so you can work more comfortably. A power-line reel to keep the power cable organized. Holds up to 1.6 gal of solution so you waste less time refilling.

(hold down “**Ctrl**” key on your keyboard while clicking on the YouTube link below)

<https://www.youtube.com/watch?v=85gnW8Q9mYY>